2018

CEILING FANS







CEILING FANS

TERMS & CONDITIONS

١.	Terms	the state where the obligation is payable.
2.	Ordering	Written or faxed orders are requested. Minimum quantity requirements may vary from product to product.
3.	Minimum Order	\$100 per shipment. Will-call orders \$100.00. Orders less than the minimum are subject to a \$10.00 fee.
4.	Shipments	Specify on your order whether the shipment is to be made by UPS or Truck lines. Where no instructions are given, our shipping department will use its best judgment. Please note that we can not pack our product sufficiently to stop all damage by this type of carrier. The receipt of the goods must check in all orders for damage at the time of receipt. E Lighting assumes no responsibility for damage not noted at the time of delivery.
5.	Drop Shipments	E Lighting (shipper) assumes no responsibility for damage or shortages on any Drop shipment that the recipient does not note on the freight bill. All drop shipments are shipped FOB at the point of shipment. Any goods received with damages are to be reported upon receipt to the carrier and a claim filed with them. The carrier is responsible for loss or breakage in transit, not the shipper. All drop ship orders are subject to a minimum fee of \$6.00 per bill of lading.
6.	Freight Claims	Should any damage occur in transit DO NOT REFUSE TO ACCEPT THE SHIPMENT, as this causes you unnecessary shipping expense and delay. Any goods received with damages are to be reported upon receipt to the carrier and a claim filed with them. The carrier is responsible for loss or breakage in transit, not the shipper.
7.	Returns	No merchandise is to be returned without prior authorization. Call 1-855-500-8882 & ask Customer Service for a return authorization.
8.	Claims	All claims must be made in writing within 10 days after receipt of merchandise. All shipments should be inspected for damage upon delivery. E Lighting is not responsible for merchandise not inspected at the time of delivery.
9.	Freight Policy	All orders are shipped freight collect unless prior arrangements have been made. All prepaid shipments must be paid within terms or loss of freight allowance will occur.
10.	Prices	Receive our best price by ordering in standard cartons. Our prices are subject to change without notice. Pricing levels include Non-Distributor, Distributor and Master Distributor.
11.	Non-Stock	Purchaser understands that all non-stock, special, custom, or modified versions of normal factory-stock items are not returnable.

All accounts subject to a late penalty of 1 1/2% per month on all invoices that exceed 30 days. But in no event higher than permitted by law in

Limited Warranty: All fixtures and products manufactured by E Lighting are warranted to be free from defects in workmanship and materials, as manufactured, for a period of Two full years from date of invoice. The illustrations and descriptions of the products also shown herein are for the sole purpose of identification and are not intended to imply that the products will fit any particular purpose or necessarily conform to the illustrations and/or the description.

Implied Labor Warranty

E Lighting will not accept any liability for labor claims, loss of profit, repairs or any other expenses incidental to replacement. The limited warranty of E Lighting brand lighting products is expressly in lieu of all other warranties, express, statuary or implied including the warranty of merchantability and fitness for a particular purpose.

Product Warranty

Terms

WARRANTY - ALL products in this catalog, other than our LED fixtures which has a Limited Power Supply warranty (Module, PC Board Diodes and Drivers) for three (3) years, are warranted to be free of defects in material and workmanship for one (1) year from date of purchase. This warranty is Limited to the correction of any such defect, or the replacement of any such defective item, provided that: (a) item(s) was (were) purchased from an authorized E Lighting distributor; (b) we are properly notified and consent to the return of the item(s) in question: (c) the item(s) is/are returned with proof of purchase date; and (d) it is found upon inspection by us that the item(s) is/are defective as noted above. This warranty does not cover Labor costs or consequential damages, nor does it apply to any item(s) that has/have been improperly installed, overloaded, altered, or otherwise abused by the customer, its agent(s) or employee(s).

ALL finishes have a Limited warranty for three (3) years, are specifically excluded from the terms of this warranty since they are subject to environmental and maintenance damages beyond our control. Other than the described obligation, we assume no further Liability with respect to the sale or use of our products. We make no warranty, express or implied, and disclaim any warranty of merchantability or fitness for a particular purpose.

SUMMARY





































SUMMARY



















































SUMMARY


















































THE MANHATTANTM



Specificati	on Features	
Hanging:	Aluminum Ball with 7" Downrod	
Housing:	320mm Steel Housing	
Lead Wire:	54" Lead Wire	
UL Listing:	Indoor Locations	
Blade Span:	(5) 52" Plywood Paper Overlay	
Motor Size:	172 x 18mm	
Motor Style:	Silicon Steel - High Performance	
Speeds:	3 Speeds - Reversible	
Rotation:	115mm steel top yoke cover - slide reversing switch	
Capacitor:	Triple-Capacitor	
Light Kit:	10" Diameter Frosted Glass (2) E26 Sockets (2) 13W CFL lamps Included	
Voltage:	120V	
Control:	Wall Control	
Instructions:	Easy to Follow & Illustrated	
Warranty:	Limited Lifetime All other components of our fan, plus light kits, and electronics are covered by a 1 year warranty	



The $Manhattan^{TM}$ fan delivers contemporary style with maximum comfort and excellent value.

Performance & Energy Information			
Fan Speed	CFM	Watts	CFM/Watt
High	5156	60.3	85.5
Medium	3561	38.3	92.9
Low	2771	19.7	140

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
F804BN	Brushed Nickel	Black	Black	
F804WH	White	White	White	

THE GENEVATM



The Geneva[™] fan delivers European style with an essence of class and destination.

Performance & Energy Information			
Fan Speed	CFM	Watts	CFM/Watt
High	5695	59	97
Medium	3841	28	136
Low	2889	11	208

Specificati	on Features		
Hanging:	Aluminum Ball with 4.5" Downrod		
Housing:	250mm Steel Housing		
Lead Wire:	54" Lead Wire		
UL Listing:	Indoor Locations		
Blade Span:	(5) 52" MDF Paper Overlay 12° Pitch		
Motor Size:	153 x 18mm		
Motor Style:	Silicon Steel - High Performance		
Speeds:	3 Speeds - Reversible		
Rotation:	115mm steel top yoke cover - slide reversing switch		
Capacitor:	Triple-Capacitor		
Light Kit:	9" Diameter Frosted Glass (2) GU24 Sockets Lamps not included		
Voltage:	120V		
Control: Pull Chain or Wall Control			
Instructions:	Easy to Follow & Illustrated		
Warranty:	Limited Lifetime All other components of our fan, plus light kits, and electronics are covered by a 1 year warranty		

Item Num	er Finish	Blade Side 1	Blade Side 2	Blade Options
F836BN	Brushed Nicke	el Black	Black	



Specification Features			
Hanging:	Aluminum Ball with 6" Downrod		
Housing:	250mm Steel Housing		
Lead Wire:	54" Lead Wire		
UL Listing:	Indoor Locations		
Blade Span:	(3) 52" MDFPaper Overlay		
Motor Size:	153 x 18mm		
Motor Style:	Silicon Steel - High Performance		
Speeds:	3 Speeds - Reversible		
Rotation:	115mm steel top yoke cover - slide reversing switch		
Capacitor:	Triple-Capacitor		
Light Kit:	9" Diameter Frosted Glass (2) GU24 Sockets Lamps not included		
Voltage:	120V		
Control:	Wall Control		
Instructions:	Easy to Follow & Illustrated		
Warranty:	Limited Lifetime All other components of our fan, plus light kits, and electronics are covered by a 1 year warranty		

The *Brentwood*[™] fan motors receive a 100% quality control inspection twice during production plus several more post-production QC inspections

Performance & Energy Information				
Fan Speed	CFM	Watts	CFM/Watt	
High	5313	54.6	97	
Medium	3363	25.0	134	
Low	2060	9.3	221	

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
F800BN	Brushed Nickel	Black	Black	

THE MONTERAYTM



The *Monteray*™ fan delivers European style with an essence of class and destination.

Performance & Energy Information			
Fan Speed	CFM	Watts	CFM/Watt
High	5420	65	83
Medium	3450	33	105
Low	2300	13	177

Specification Features			
Hanging:	Aluminum Ball with 4.5" Downrod		
Housing:	250mm Steel Housing		
Lead Wire:	54" Lead Wire		
UL Listing:	Indoor Locations		
Blade Span:	(3) 52" MDF Paper Overlay 12° Pitch		
Motor Size:	153 x 18mm		
Motor Style:	Silicon Steel - High Performance		
Speeds:	3 Speeds - Reversible		
Rotation:	115mm steel top yoke cover - slide reversing switch		
Capacitor:	Triple-Capacitor		
Light Kit:	9" Diameter Frosted Glass (2) GU24 Sockets Lamps not included		
Voltage:	120V		
Control:	Wall Control		
Instructions:	Easy to Follow & Illustrated		
Warranty:	Limited Lifetime All other components of our fan, plus light kits, and electronics are covered by a 1 year warranty		

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
F834BN	Black	Black	Black	

THE VIENNATM



Specification Features			
Hanging:	Aluminum Ball with 4.5" Downrod		
Housing:	250mm Steel Housing		
Lead Wire:	54" Lead Wire		
UL Listing:	Indoor Locations		
Blade Span:	(4) 42" MDF Paper Overlay 12° Pitch		
Motor Size:	153 x 10mm		
Motor Style:	Silicon Steel - High Performance		
Speeds:	3 Speeds - Reversible		
Rotation:	115mm steel top yoke cover - slide reversing switch		
Capacitor:	Triple-Capacitor		
Light Kit:	7" Diameter Frosted Glass 10W Integrated LED 750 Lumens		
Voltage:	120V		
Control:	Wall Control		
Instructions:	Easy to Follow & Illustrated		
Warranty:	Limited Lifetime All other components of our fan, plus light kits, and electronics are covered by a 1 year warranty		

The Vienna[™] fan delivers European style with an essence of class and destination.

Performance & Energy Information					
Fan Speed CFM Watts CFM/Watt					
High	4200	52	81		
Medium	3100	31	100		
Low	2050	13	158		

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
F832BN	Brushed Nickel	Light Oak	Light Oak	

MODERN FAN

THE APOLLOTM





The Apollo™ fan delivers maximum comfort and excellent value. This moderately priced fan proves that practical needs can be met without sacrificing appearance.

Performance & Energy Information					
Fan Speed CFM Watts CFM/Watt					
High	5133.22	61	84.15		
Medium	3828.88	33.4	114.64		
Low	2321.45	13.6	170.69		

Specification Features			
Hanging:	Die Cast Ball and Bracket with 4" Downrod		
Housing:	230mm Steel Housing		
Lead Wire:	54" Lead Wire		
UL Listing:	Indoor Locations		
Blade Span:	(4) 52"		
Motor Size:	153 x 18mm		
Motor Style:	High Quality		
Speeds:	3 Speeds - Reversible		
Rotation: 150mm			
Capacitor:	Triple-Capacitor		
Light Kit: Adaptable Not Included			
Voltage:	120V		
Control:	Pull Chain		
Instructions:	Easy to Follow & Illustrated		
Warranty:	Limited Lifetime All other components of our fan, plus light kits, and electronics are covered by a 1 year warranty		

6

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
F822BN	Brushed Nickel	White	Maple	
F8220RB	Oil Rubbed Bronze	Maple	Rosewood	

THE MILAN™



Specification Features Aluminum Ball with 4.5" Downrod Hanging: 250mm Steel Housing Housing: Lead Wire: 54" Lead Wire **UL Listing:** Indoor Locations Blade Span: (5) 52" MDF Paper Overlay 12° Pitch Motor Size: 153 x 15mm Motor Style: Silicon Steel - High Performance Speeds: 3 Speeds - Reversible 115mm steel top yoke cover - slide Rotation: reversing switch Capacitor: Triple-Capacitor 9" Diameter Frosted Glass Light Kit: 20W Integrated LED 1500 Lumens 120V Voltage: Control: Wall Control Instructions: Easy to Follow & Illustrated Limited Lifetime All other components of our fan, plus light Warranty: kits, and electronics are covered by a 1 year warranty

The *Milan*™ fan delivers contemporary syle with maximum comfort and excellent value.

Performance & Energy Information					
Fan Speed CFM Watts CFM/Watt					
High	5800	60	97		
Medium	3911	27	145		
Low	2471	11.5	215		

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
F840BN	Brushed Nickel	Light Oak	Light Oak	

EL PRESIDENTE™



The *El Presidente*™ fan delivers transitional styling with maximum comfort and excellent value... The fan is built for performance and design for easy and secure installation.

Performance & Energy Information					
Fan Speed CFM Watts CFM/Watt					
High	5419	65.1	83.3		
Medium 3454 32.3 107					
Low	2306	11.8	195		

Specification Features			
Hanging:	Die Cast Ball and Bracket with 4" Downrod		
Housing:	ing: 230mm Steel Housing		
Lead Wire:	54" Lead Wire		
UL Listing:	Indoor Locations		
Blade Span:	(5) 52"		
Motor Size:	153 x 18mm		
Motor Style:	High Quality		
Speeds: 3 Speeds - Reversible			
Rotation: 150mm			
Capacitor:	Triple-Capacitor		
Light Kit: Adaptable Not Included			
Voltage:	120V		
Control:	Wall Control		
Instructions:	Easy to Follow & Illustrated		
Warranty:	Limited Lifetime All other components of our fan, plus light kits, and electronics are covered by a 1 year warranty		

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
F822BN	Brushed Nickel	Brushed Nickel	Brushed Nickel	
F8220RB	Oil Rubbed Bronze	Walnut	Washed Oak	

TRANSITIONAL FAN

THE REAGANTM



Specificati	on Features		
Hanging:	Aluminum Ball with 4" Downrod		
Housing:	130mm Steel Housing		
Lead Wire:	24" Lead Wire		
UL Listing:	Indoor Locations		
Blade Span:	(5) 52" MDF Paper Overlay 12° Pitch		
Motor Size:	153 x 12mm		
Motor Style:	Silicon Steel - High Quality		
Speeds:	3 Speeds - Reversible		
Rotation:	100mm Switch Housing		
Capacitor:	Triple-Capacitor		
Light Kit:	10" Diameter Frosted Glass (1) E12 Socket		
Voltage:	120V		
Control:	Wall Control		
Instructions:	Easy to Follow & Illustrated		
Warranty:	Limited Lifetime All other components of our fan, plus light kits, and electronics are covered by a 1 year warranty		



Performance & Energy Information						
Fan Speed	Fan Speed CFM Watts CFM/Watt					
High	5419	65.1	83.3			
Medium	3454	32.3	107			
Low	Low 2306 11.8 195					

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
F806BN	Brushed Nickel	Dark Cherry	Mahogany	
F806WH	White	White	Washed Oak	
F806ORB	Oil Rubbed Bronze	Dark Cherry	Walnut	

TRANSITIONAL FAN

THE LINCOLNTM





The *Lincoln*™ fan delivers transitional styling with maximum comfort and excellent value... The fan is built for performance and design for easy and secure installation.

Performance & Energy Information							
Fan Speed	Fan Speed CFM Watts CFM/Watt						
High	5232	57.4	91.15				
Medium	3496	33	105.94				
Low	Low 2254 13.6 165.74						

Specificati	on Features		
Hanging:	Dual Mount Aluminum Ball with 4" Downrod		
Housing:	300mm Steel Housing		
Lead Wire:	54" Lead Wire		
UL Listing:	Indoor Locations		
Blade Span:	(5) 52" Plywood Paper Overlay 14° Pitch		
Motor Size:	153 x 18mm		
Motor Style:	High Quality		
Speeds:	3 Speeds - Reversible		
Rotation:	120mm Switch Housing		
Capacitor:	Triple-Capacitor		
Light Kit:	Adaptable Not Included		
Voltage:	120V		
Control:	Pull Chain		
Instructions:	Easy to Follow & Illustrated		
Warranty:	Limited Lifetime All other components of our fan, plus light kits, and electronics are covered by a 1 year warranty		

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
F810BN	Brushed Nickel	Brushed Nickel	Brushed Nickel	
F8100RB	Oil Rubbed Bronze	Dark Cherry	Walnut	

THE SOUTH BEACH™



Specificati	Specification Features			
Hanging:	Aluminum Ball with 4" Downrod			
Housing:	220mm Steel Housing			
Lead Wire:	24" Lead Wire			
UL Listing:	Indoor Locations			
Blade Span:	(3) 52" MDF Paper Overlay 14° Pitch			
Motor Size:	153 x 15mm			
Motor Style:	Silicon Steel - High Quality			
Speeds:	3 Speeds - Reversible			
Rotation:	100mm Switch Housing			
Capacitor:	Triple-Capacitor			
Light Kit:	Adaptable, Not Included			
Voltage:	120V			
Control:	Pull Chain			
Instructions:	Easy to Follow & Illustrated			
Warranty:	Limited Lifetime All other components of our fan, plus light kits, and electronics are covered by a 1 year warranty			



Performance & Energy Information					
Fan Speed	Fan Speed CFM Watts CFM/Watt				
High	5585	60.5	92.3		
Medium	3781	27.4	137		
Low	2751	10.5	262		

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
F808BN	Brushed Nickel	Brushed Nickel	Brushed Nickel	BK

TRADITIONAL HUGGER FAN



The Van Buren™ with it's smooth style, traditional look, and high performance makes it appropriate for any decor.

Performance & Energy Information						
Fan Speed	CFM	Watts	CFM/Watt			
High						
Medium						
Low						

Specification Features			
Hanging:	Dual Mount Aluminum Ball with 4" Downrod		
Housing:	220mm Steel Housing		
Lead Wire:	54" Lead Wire		
UL Listing:	Indoor Locations		
Blade Span:	(5) 52" MDF Paper Overlay 14° Pitch		
Motor Size:	153 x 15mm		
Motor Style:	High Quality		
Speeds:	3 Speeds - Reversible		
Rotation:	120mm Switch Housing		
Capacitor:	Triple-Capacitor		
Light Kit:	9" Diameter Frosted Glass (2) GU24 Sockets		
Voltage:	120V		
Control:	Pull Chain		
Instructions:	Easy to Follow & Illustrated		
Warranty:	Limited Lifetime All other components of our fan, plus light kits, and electronics are covered by a 1 year warranty		

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
F826BN	Brushed Nickel	Brushed Nickel	Brushed Nickel	
F826ORB	Oil Rubbed Bronze	Dark Cherry	Walnut	

TRADITIONAL HUGGER FAN

THE FILLMORETM



Specification Features			
Hanging:	Aluminum Ball with 4" Downrod		
Housing:	220mm Steel Housing		
Lead Wire:	54" Lead Wire		
UL Listing:	Indoor Locations		
Blade Span:	(5) 52" MDF Paper Overlay 14° Pitch		
Motor Size:	153 x 15mm		
Motor Style:	Silicon Steel - High Quality		
Speeds:	3 Speeds - Reversible		
Rotation:	120mm Switch Housing		
Capacitor:	Triple-Capacitor		
Light Kit:	Adaptable, Not Included		
Voltage:	120V		
Control:	Pull Chain		
Instructions:	Easy to Follow & Illustrated		
Warranty:	Limited Lifetime All other components of our fan, plus light kits, and electronics are covered by a 1 year warranty		

Performance & Energy Information						
Fan Speed CFM Watts CFM/Watt						
High						
Medium						
Low						

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
F828ORB	Oil Rubbed Bronze	Walnut	Washed Oak	

TRADITIONAL FAN

THE BLUE NORTHER™





Performance & Energy Information						
Fan Speed CFM Watts CFM/Watt						
High	5232	57.4	91.15			
Medium	105.94					
Low	Low 2254 13.6 165.74					

Specification Features			
Hanging:	Dual Mount Aluminum Ball with 4" Downrod		
Housing:	220mm Steel Housing		
Lead Wire:	54" Lead Wire		
UL Listing:	Indoor Locations		
Blade Span:	(5) 52" 12° Pitch		
Motor Size:	153 x 13mm		
Motor Style:	High Quality		
Speeds:	3 Speeds - Reversible		
Rotation:	100mm Switch Housing		
Capacitor:	Triple-Capacitor		
Light Kit:	Adaptable, Not Included		
Voltage:	120V		
Control:	Pull Chain		
Instructions:	Easy to Follow & Illustrated		
Warranty:	Limited Lifetime All other components of our fan, plus light kits, and electronics are covered by a 1 year warranty		

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
ESD552BN	Brushed Nickel	Cherry	Oak	
ESD552PB	Polished Brass	Walnut	Cherry	
ESD552WH	White	White	White	

TRADITIONAL HUGGER FAN

THE PARKER™



Specificati	on Features		
Hanging:	Hugger Mount		
Housing:	280mm Steel Housing		
Lead Wire:	12" Lead Wire		
UL Listing:	Indoor Locations		
Blade Span:	(5) 52" MDF Paper Overlay 12° Pitch		
Motor Size:	153 x 13mm		
Motor Style:	Silicon Steel - High Quality		
Speeds:	3 Speeds - Reversible		
Rotation:	120mm Switch Housing		
Capacitor:	Triple-Capacitor		
Light Kit:	Adaptable, Not Included		
Voltage:	120V		
Control:	Pull Chain		
Instructions:	Easy to Follow & Illustrated		
Warranty:	Limited Lifetime All other components of our fan, plus light kits, and electronics are covered by a 1 year warranty		



Performance & Energy Information					
Fan Speed CFM Watts CFM/Watt					
High	5232	57.4	91.15		
Medium	3496	33	105.94		
Low	2254	13.6	165.74		

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
F704BN	Brushed Nickel	Cherry	Oak	
F704WH	White	White	White	
F704PB	Polished Brass	Walnut	Cherry	

TRADITIONAL HUGGER FAN

THE HAMILTON™







Performance & Energy Information						
Fan Speed CFM Watts CFM/Watt						
High	3887	46.8	83			
Medium 2736 33.3 82.1						
Low 2051 23.5 87.2						

Specificati	ion Features	
Hanging:	Hugger Mount	
Housing:	280mm Steel Housing	
Lead Wire:	12" Lead Wire	
UL Listing:	Indoor Locations	
Blade Span:	(5) 42" 12° Pitch	
Motor Size:	153 x 12mm	
Motor Style:	High Quality	
Speeds:	ds: 3 Speeds - Reversible	
Rotation: 100mm Switch Housing		
Capacitor:	Triple-Capacitor	
Light Kit:	Adaptable, Not Included	
Voltage:	120V	
Control:	Pull Chain	
Instructions:	Easy to Follow & Illustrated	
Warranty:	Limited Lifetime All other components of our fan, plus light kits, and electronics are covered by a 1 year warranty	

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
F710WH	White	White	White	
F712WH	White	White	White	
F714WH	White	White	White	

TRADITIONAL FAN

THE DENTON™



Limited Lifetime

warranty

Warranty:

All other components of our fan, plus light

kits, and electronics are covered by a 1 year



Performance & Energy Information										
Fan Speed CFM Watts CFM/Watt										
High	3887	46.8	83							
Medium	2736	33.3	82.1							
Low	2051	23.5	87.2							

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
F720BN	Brushed Nickel	Maple	White	
F720WH	White	White	Washed Oak	
F720PORB	Oil Rubbed Bronze	Walnut	Washed Pine	

OUTDOOR FAN





Specificati	on Features
Hanging:	Dual Mount Aluminum Ball with 5" Downrod
Housing:	280mm Steel Housing
Lead Wire:	54" Lead Wire
UL Listing:	OutdoorLocations
Blade Span:	(5) 52" ABS 12° Pitch
Motor Size:	153 x 13mm
Motor Style:	Silicon Steel - High Quality
Speeds:	3 Speeds - Reversible
Rotation:	100mm Switch Housing
Capacitor:	Triple-Capacitor
Light Kit:	Adaptable, Not Included
Voltage:	120V
Control:	Pull Chain
Instructions:	Easy to Follow & Illustrated
Warranty:	Limited Lifetime All other components of our fan, plus light kits, and electronics are covered by a 1 year warranty



Performance & Energy Information										
Fan Speed	CFM/Watt									
High	5172	57.4	90							
Medium	3486	33.2	105							
Low	2257	13.3	169							

Item Number	Finish	Blade Side 1	Blade Side 2	Blade Options
F600BN	Brushed Nickel	Maple	Maple	
F602BK	Black	Black	Black	
F604WH	White	White	White	
F606ORB	Oil Rubbed Bronze	Oil Rubbed Bronze	Oil Rubbed Bronze	



9330

- Brushed Nickel, Oil Rubbed Bronze, or White
- (1) E26 or GU24 Socket for A-19 Lamp
- · Opal Glass
- · Lamps Sold Separately

9620

- Brushed Nickel, Oil Rubbed Bronze, or White
- (2) E26 or GU24 Sockets for A-19 Lamp
- Frost White Glass
- · Lamps Sold Separately





9345

- Brushed Nickel, Oil Rubbed Bronze, or White
- (2) E26 or GU24 Sockets for A-19 Lamp
- · Alabaster Glass
- Lamps Sold Separately

Item Number	Socket	Lamp Type	Wattage	Recommended Lamp	Voltage	Avail. Finishes	Kelvin	Lumens	CRI	Rated Hours
INC9330	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9330	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9330	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9345	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9345	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9345	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9620	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9620	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9620	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000



9370

- Brushed Nickel, or Oil Rubbed Bronze
- (2) E26 or GU24 Sockets for A-19 Lamp
- Frost White Glass
- · Lamps Sold Separately



9334

- Brushed Nickel, Oil Rubbed Bronze, or White
 (1) E26 or GU24 Socket for A-19 Lamp
- Opal Glass
- · Lamps Sold Separately



9342

- Brushed Nickel, Oil Rubbed Bronze, or White
- (1) E26 or GU24 Socket for A-19 Lamp Tuscan Scavo Glass
- · Lamps Sold Separately



9348

Brushed Nickel, Oil Rubbed Bronze, or White
(1) E26 or GU24 Socket for A-19 Lamp
Alabaster Glass

20

- · Lamps Sold Separately

Item Number	Socket	Lamp Type	Wattage	Recommended Lamp	Voltage	Avail. Finishes	Kelvin	Lumens	CRI	Rated Hours
INC9334	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9334	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9334	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9342	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9342	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9342	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9348	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL93428	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9348	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9370	E26	INC	60	B11018	120	BN, ORB	27K	545	80	5,000
CFL9370	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB	27K	600	82	10,000
LED9370	GU24	LED	7	B1006	110-277	BN, ORB	28K	450	75	40,000



- Brushed Nickel, White, or Oil Rubbed Bronze
- (2) E26 or GU24 Sockets for A-19 Lamp
- Frost White Glass
- · Lamps Sold Separately



- Brushed Nickel, White, or Oil Rubbed Bronze
- (2) E26 or GU24 Sockets for A-19 Lamp
- · Tuscan Scavo Glass
- · Lamps Sold Separately



- Brushed Nickel, White, or Oil Rubbed Bronze
- (2) E26 or GU24 Sockets for A-19 Lamp
- Opal Glass
- · Lamps Sold Separately






Light kits on this page are supplied with BN, ORB, and WH fitters.



9566

- Brushed Nickel, White, or Oil Rubbed Bronze
- (2) E26 or GU24 Sockets for A-19 Lamp
- Opal Glass
- · Lamps Sold Separately



- (2) E26 or GU24 Sockets for A-19 Lamp
- Tudscan Scavo Glass
- · Lamps Sold Separately

Item Number	Socket	Lamp Type	Wattage	Recommended Lamp	Voltage	Avail. Finishes	Kelvin	Lumens	CRI	Rated Hours
INC9546	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9546	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9546	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9548	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9548	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9548	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9550	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9550	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9550	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9564	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9564	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9564	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9566	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9566	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9566	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000

OUTDOOR FAN LIGHT KITS



9610

- Brushed Nickel, Oil Rubbed Bronze, or White
- (1) E26 or GU24 Socket for A-19 Lamp
- · White Opal Glass
- · Lamps Sold Separately

9612

- · Brushed Nickel, Oil Rubbed Bronze, or White
- (2) E26 or GU24 Sockets for A-19 Lamp
- · AWhite Opal Glass
- · Lamps Sold Separately





9614

- Brushed Nickel, Oil Rubbed Bronze, or White
- (2) E26 or GU24 Sockets for A-19 Lamp
- White Opal Glass
- · Lamps Sold Separately

Item Number	Socket	Lamp Type	Wattage	Recommended Lamp	Voltage	Avail. Finishes	Kelvin	Lumens	CRI	Rated Hours
INC9610	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9610	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9610	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9612	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9612	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9612	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9614	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9614	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9614	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000



9070

- 6.5" Schoolhouse Light Kit for 42" Fan
- Brushed Nickel, White, or Oil Rubbed Bronze
- (1) E26 or GU24 Sockets for A-19 Lamp
- White Opal Glass
- 6.5" Diameter
- · Lamps Sold Separately



9300

- ullet 8" Schoolhouse Light Kit for 52" Fan
- Brushed Nickel, White, or Oil Rubbed Bronze
- (1) E26 or GU24 Sockets for A-19 Lamp
- White Opal Glass
- · 8" Diameter
- · Lamps Sold Separately



9002

- Brushed Nickel, White, or Oil Rubbed Bronze
- (1) E26 or GU24 Socket
- 3.875" Fitter
- · Glass Sold Separately
- · Lamps Sold Separately



9003

- Brushed Nickel, White, or Oil Rubbed Bronze
- (1) E26 or GU24 Socket
- · Glass Sold Separately
- Lamps Sold Separately

Item Number	Socket	Lamp Type	Wattage	Recommended Lamp	Voltage	Avail. Finishes	Kelvin	Lumens	CRI	Rated Hours
INC9002	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9002	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9002	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9003	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9003	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9003	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9070	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9070	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9070	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9300	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9300	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9300	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000



*Shown with 252-Alabaster Glass, sold separately

9026

- Brushed Nickel, White, or Oil Rubbed Bronze
- (3) E26 or GU24 Sockets
- · Glass Sold Separately
- · Lamps Sold Separately



9028

- Brushed Nickel, White, or Oil Rubbed Bronze
- (4) E26 or GU24 Sockets
- Glass Sold Separately
- · Lamps Sold Separately



9325

- Brushed Nickel, White, or Oil Rubbed Bronze
- (4) E26 or GU24 Sockets
- Lamps Sold Separately



9050

- Brushed Nickel, White, or Oil Rubbed Bronze
- (4) E26 or GU24 Sockets
- · Glass Sold Separately
- · Lamps Sold Separately

FAN FITTER OPTIONAL GLASS

Add desired glass part number to the end of the fitter part number in your order for a completely customized light kit.



003

Clear Ribbed



252

Alabaster



250

White Opal



270

Tuscan Scavo

Item Number	Socket	Lamp Type	Wattage	Recommended Lamp	Voltage	Avail. Finishes	Kelvin	Lumens	CRI	Rated Hours
INC9026	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9026	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9026	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9028	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9028	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9028	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9050	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9050	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9050	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000
INC9325	E26	INC	60	B11018	120	BN, ORB, WH	27K	545	80	5,000
CFL9325	GU24	CFL	13	LVC-13-SP-27	120	BN, ORB, WH	27K	600	82	10,000
LED9325	GU24	LED	7	B1006	110-277	BN, ORB, WH	28K	450	75	40,000

REMOTE & WALL CONTROLS





EPRC-110

Universal Remote Control Set

- 3 speed control
- Black receiver
- · Available in White or Almond
- · Adaptable to both dimmer and on/off use
- Does not work with GU24 lamps
- 1 9v battery (included)





EPRC-112

Remote Wall Control Set

- 3 speed control
- Black receiver
- · Available in White or Almond
- · Adaptable to both dimmer and on/off use
- Does not work with GU24 lamps
- 1 12v battery (included)



EPWS-200

Fan & Light Wall Control

- 4 Speed
- 3 Level light slide bar control
- · White Finish
- For use with incandescent lamps only



EPWS-202

Fan & Light Wall Control

- 3 speed control
- On/Off light control
- White finish

FAN ACCESSORIES



Knob



Walnut Wooden

Knob







107012 Natural Wooden Handle







107010 Gold Tassel















107024PB Polished Brass Bell Connector







107021BK 500' Black Brass Chain



107021AB 100' Antique Brass Chain



107021PB 100' Polished Brass Chain



107021BN 100' Brushed Nickel Chain

FAN BLADE COLOR OPTONS



Black



Brushed Nickel



White



Walnut



Rosewood



Cherry



Mahogany



Dark Cherry



Oak



Maple



Washed Oak



Bleached Oak



Light Oak



Pickled Oak



Washed Pine

OLD/NEW WORK FAN BOX & SUPPORT



EPFB101

New Work fan/fixture box. All metallic. Pre-assembled outlet box. Bar adjust 16-24" for accessible ceiling joists. Max weight for fans: 200 lbs. Max weight for fixturs: 70 lbs. NEC and UL compliant for fan support.



EPFB102

Old Work fan/fixture box. All metallic. Pre-assembled outlet box. Bar adjust 16-24" for accessible ceiling joists. Max weight for fans: 50 lbs. Max weight for fixturs: 35 lbs. NEC and UL compliant for fan support.

LAMPS



60 Watt • E26 Base • 545 Lumens 750 Rated Hrs.



LVC-13-SP-2713 Watt • GU24 Base • 27K
800 Lumens • 10,000 Rated Hrs.



B1006 7 Watt • GU24 Base • 27K 700 Lumens • 50,000 Rated Hrs.



B1002 7 Watt • E26 Base • 27/41K 700 Lumens • 50,000 Rated Hrs.



B2107 7 Watt • GU24 Base • 27/41K 700 Lumens • 50,000 Rated Hrs.

INDEX

003	pg.	24	EPRC-110	pg.	25
250	pg.	24	EPRC-112	pg.	25
252	pg.	24	EPWS-200	pg.	25
270	pg.	24	EPWS-202	pg.	25
6920	pg.	19	ESD552	pg.	14
9002	pg.	23	F600	pg.	18
9003	pg.	23	F602	pg.	18
9026	pg.	24	F604	pg.	18
9028	pg.	24	F606	pg.	18
9050	pg.	24	F704	pg.	15
9070	pg.	23	F710	pg.	16
9300	pg.	23	F720	pg.	17
9325	pg.	24	F800	pg.	3
9330	pg.	19	F804	pg.	1
9334	pg.	20	F806	pg.	9
9342	pg.	20	F808	pg.	11
9345	pg.	19	F810	pg.	10
9348	pg.	20	F822	pg.	6
9370	pg.	20	F822	pg.	8
9546	pg.	21	F826	pg.	12
9548	pg.	21	F828	pg.	13
9550	pg.	21	F832	pg.	5
9564	pg.	21	F834	pg.	4
9566	pg.	21	F836	pg.	2
9610	pg.	22	F840	pg.	7
9612	pg.	22			
9614	pg.	22			
107010	pg.	26			
107011	pg.	26			
107012	pg.	26			
107014	pg.	26			
107015	pg.	26			
107016	pg.	26			
107021	pg.	26			
107022	pg.	26			
107024	pg.	26			
107080	pg.	26			
107082	pg.	26			
EPFB101	pg.	27			
EPFB102	pg.	27			

CEILING FANS

2018





